



US007182736B2

(12) **United States Patent**
Roy et al.

(10) **Patent No.:** **US 7,182,736 B2**
(45) **Date of Patent:** ***Feb. 27, 2007**

(54) **APPARATUS AND METHOD FOR ASSESSING LOADS ON ADJACENT BONES**

(75) Inventors: **Shuvo Roy**, Cleveland, OH (US); **Aaron J. Fleischman**, University Heights, OH (US); **Edward C. Benzel**, Gates Mills, OH (US); **Lisa Ferrara**, Cleveland Heights, OH (US)

(73) Assignee: **Cleveland Clinic Foundation**, Cleveland, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 309 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/769,823**

(22) Filed: **Feb. 2, 2004**

(65) **Prior Publication Data**

US 2004/0186396 A1 Sep. 23, 2004

Related U.S. Application Data

(63) Continuation of application No. 09/939,331, filed on Aug. 24, 2001, now Pat. No. 6,706,005.

(60) Provisional application No. 60/228,166, filed on Aug. 25, 2000.

(51) **Int. Cl.**

A61B 5/117 (2006.01)

A61B 5/103 (2006.01)

(52) **U.S. Cl.** **600/587**

(58) **Field of Classification Search** **600/587**,
600/594, 300; 435/174, 176, 177, 180, 181;
436/518, 524, 528, 531; 424/178.1; 530/402,
530/815, 810-812; 623/16, 17

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,425,775 A 6/1995 Kovacevic et al.
5,456,724 A 10/1995 Yen et al.

(Continued)

OTHER PUBLICATIONS

IEEE Transactions on Biomedical Engineering, vol. 47, No. 1, Jan. 2000 "A Portable Microsystem-Based Telemetric Pressure and Temperature Measurement Unit", Bernd B. Flick and Reinhold Orgimeister.

Med. Eng. Phys. vol. 19, No. 6, pp. 539-549, 1997 "Comparison of Loads on Internal Spinal Fixation Devices Measured in Vitro and in Vivo", A. Rohlmann, G. Bergmann, F. Graichen and U. Weber.

(Continued)

Primary Examiner—Max F. Hindenburg

Assistant Examiner—Brian Szmaj

(74) *Attorney, Agent, or Firm*—Tarolli, Sundheim, Covell & Tummino LLP

(57) **ABSTRACT**

An apparatus (10) that utilizes microelectromechanical systems (MEMS) technology to provide an in vivo assessment of loads on adjacent bones (24 and 26) comprises a body (34) for insertion between the adjacent bones. At least one sensor (42) is associated with the body (34). The sensor (42) generates an output signal in response to and indicative of a load being applied to the body (34) through the adjacent bones (24 and 26). A telemetric device (40) is operatively coupled with the sensor (42). The telemetric device (40) is operable to receive the output signal from the sensor (42) and to transmit an EMF signal dependent upon the output signal. According to various aspects of the invention, the sensor comprises a pressure sensor (42), a load cell (320), and/or at least one strain gauge (142).

13 Claims, 8 Drawing Sheets

