



US007359554B2

(12) **United States Patent**
Klingensmith et al.

(10) **Patent No.:** **US 7,359,554 B2**
(45) **Date of Patent:** ***Apr. 15, 2008**

(54) **SYSTEM AND METHOD FOR IDENTIFYING A VASCULAR BORDER**

(75) Inventors: **Jon D. Klingensmith**, Shaker Heights, OH (US); **D. Geoffrey Vince**, Avon Lake, OH (US); **Anuja Nair**, Cleveland Heights, OH (US); **Barry D. Kuban**, Avon Lake, OH (US)

(73) Assignee: **Cleveland Clinic Foundation**, Cleveland, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 974 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **10/649,473**

(22) Filed: **Aug. 26, 2003**

(65) **Prior Publication Data**

US 2004/0037455 A1 Feb. 26, 2004

Related U.S. Application Data

(60) Provisional application No. 60/406,148, filed on Aug. 26, 2002, provisional application No. 60/406,183, filed on Aug. 26, 2002, provisional application No. 60/406,184, filed on Aug. 26, 2002, provisional application No. 60/406,185, filed on Aug. 26, 2002, provisional application No. 60/406,234, filed on Aug. 26, 2002, provisional application No. 60/406,254, filed on Aug. 26, 2002.

(51) **Int. Cl.**
G06K 9/48 (2006.01)

(52) **U.S. Cl.** **382/199**; 382/131; 600/467; 606/108

(58) **Field of Classification Search** 382/199, 382/128, 131; 600/467, 443, 463, 437, 462, 600/468, 585, 439, 587, 459, 485; 606/108, 606/159, 194, 191, 15

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,228,804 A 10/1980 Holasek

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 633 548 1/1995

OTHER PUBLICATIONS

Chen, C., Lu, H., Hsiao, A., "A Dual-Snake Model of High Penetrability for Ultrasound Image Boundary Extraction", *Ultrasound in Medicine and Biology*, 2001, pp. 1651-1665, vol. 27, No. 12, Elsevier, New York, U.S.A.

Primary Examiner—Sheela Chawan

(74) *Attorney, Agent, or Firm*—Leydig, Voit & Mayer Ltd

(57) **ABSTRACT**

A system and method is provided for using a first vascular image, or more particularly a plurality of control points located thereon, to identify a border on a second vascular image. Embodiments of the present invention operate in accordance with an intra-vascular ultrasound (IVUS) device and a computing device electrically connected thereto. Specifically, in one embodiment of the present invention, an IVUS console is electrically connected to a computing device and adapted to acquire IVUS data. The IVUS data (or multiple sets thereof) is then provided to (or acquired by) the computing device. In one embodiment of the present invention, the computing device includes a plurality of applications operating thereon—i.e., a border-detection application, an extrapolation application, and an active-contour application. These applications are used to (i) identify a border and control points on a first IVUS image (i.e., any IVUS image), (ii) extrapolate the control points to a second IVUS image (i.e., another IVUS image), (iii) identify a border on the second IVUS image, and (iv) adjust the border on the second IVUS image in accordance with at least one factor. In one embodiment of the present invention, the at least one factor is selected from a group consisting of gradient factor, continuity factor, and curvature factor.

20 Claims, 3 Drawing Sheets

